


55" Poseidon Rugged Freemount Monitor Product Data Sheet



- Slimline modern design
- Fully machined aluminium housing
- Full sealing up to IP65
- Full 4K resolution
- Optional PCAP multitouch screen
- Shock/vibration resistant design
- Optional rear mounted mains PSU






The Poseidon 55" Monitor is a fully ruggedized and sealed 4K resolution display suitable for a wide range of applications in the toughest of operating environments. With full sealing up to IP65 and a 700 Cd/ m sq high brightness display its highly suited for a range of harsh marine and military applications. As with all Bluestone rugged products—the internal components are protected against externally applied shock & vibrations by means of internal isolation mounts making them suitable for military vehicle, airborne—and naval solutions. Many examples of our products have been tested to 30g shock & military vibration standards and they also are listed on the Submarine Toxicity Database, item A2781 from 8.4" to 42". Various different—configurations are available so please contact us to discuss your particular requirements with one of our highly experienced engineers who can help guide you through the selection process.





55" Poseidon Rugged Freemount Monitor Product Data Sheet



Technical Specification

| Display Size | 55" Diagonal | Voltage | 24V VDC |
|----------------------|---|-------------------------|---|
| Resolution | 4K UHD 3840 x 2160 | Wonitor Voltage PSU | |
| | pixels | | 90-264 VAC 50-60Hz |
| No of Colours | 10 Bit 1.07 Billion | | |
| Interface | Displayport | Weight | 65Kg (estimated) |
| Brightness | 700 Cd/ m sq | Touch | Optional 10 Touch PCAP |
| Contrast Ratio | 5000:1 | Display and electronics | All internal components isolation mounted to protect against external shock & vibration |
| Viewing Angle | Horizontal 188°Incl, Vertical 188°Incl | | |
| Sealing | IP65 | Housing | Machined aluminium |
| Operating Temp | 0 to +50 Deg C | Finish | Hard Black anodised |
| Storage Temp | -20 to +60 Deg C | Mounting | 8 off X mount positions provided on rear of monitor |
| Power Consumption | 200W typ (estimated) | | provided of real of filofillor |

Bluestone Technology reserves the right to implement changes in design and technology which serve to improve the product. Specifications are subject to minimal alterations for production reasons. E&OE.

