24" Poseidon Xtreme Freemount Monitor Product Data Sheet



• Full Sealing up to IP67

Bluestone Technology Ltd.

- Fully machined aluminium housing
- 16:10 full 1920 x 1200 Resolution
- Shock/vibration resistant design
- Optional 1500 Cd/ m sq brightness
- Optional heaters for extended temperature operation




The Poseidon 24" Monitor is a fully ruggedised and sealed WUXGA resolution display suitable for a wide range of applications in the toughest of operating environments. With full sealing up to IP67 and a 1500 Cd/m sq brightness display its highly suited for a range of harsh environment marine and military applications. As with all Bluestone rugged products the internal components are protected against externally applied shock & vibrations by means of internal isolation mounts making them suitable for military vehicle, airborne and naval solutions. The unique feature is the resolution of 1920 x 1200 Pixels allowing a full radar sweep image to display without scaling. Many examples of our products have also been tested to 30g shock & military vibration standards and they also are also listed on the Submarine Toxicity Database, item A2781 from 8.4" to 42". Various different configurations are available so please contact us to discuss your particular requirements with one of our highly experienced engineers who can help guide you through the selection process.





24" Poseidon Rugged Freemount Monitor Product Data Sheet



Technical Specification

Display Size	24.1" Diagonal	Voltage Monitor	12V V DC, Optional wide input 10-36 VDC
Resolution	WUXGA 1920 x 1200 pixels		
		Weight	10 Kg
No of Colours	16.78 Million	Window	AR/IR filtered
Interface	DVI, VGA	Display and electronics	All internal components isolation mounted to protect against external shock & vibration
Brightness	350 Cd/ m sq		
Contrast Ratio	1300:1		
Viewing Angle	Horizontal 188°Incl, Vertical 188°Incl	Housing	Machined aluminium
		Finish	Hard Black anodised
Sealing	IP67	Mounting	Rear VESA mount, other options available, please contact to discuss
Operating Temp	-20 to +50 Deg C with optional heaters		
Storage Temp	-20 to +60 Deg C		
Power Consumption	50W (Without heater option)		

Bluestone Technology reserves the right to implement changes in design and technology which serve to improve the product. Specifications are subject to minimal alterations for production reasons. E&OE.

